











## Powerful, compact and easy to maintain

For bigger installations the belt driven CPC and CPD range has been designed in order to suit your needs. Compact, easy to install and maintain, the complete range has been designed with an eye on quality and robustness. Perfect alignment of the panels and the possibility to duct and place against a wall are the big advantages of this range.

Technology	 Screw compressor
Use	 Continuous
Noise level	 Standard: 69-74 dB(A)
FAD	 3970-12660 l/min
Power	 40-100 HP / 30-75 kW
Pressure	 8-13 bar
Weight	 680-1200 kg
Dimensions (mm)	 CPC 40: 1100 x 1365 x 1510 CPC 50: 1100 x 1365 x 1510 CPC 60: 1110 x 1365 x 1750 CPD 75: 1100 x 1955 x 1790 CPD 100: 1100 x 1955 x 1790

**CPK 5,5 – 22 HP**  
Compact Screw

**CPA/CPB 5,5 – 30 HP**  
Industrial Screw

**CPC/CPD 40 – 100 HP**  
Industrial Screw

**CPE/CPF/CPG 90 – 355 HP**  
Direct Driven Screw

**CPVR15 – 75 HP**  
Inverter Driven Screw

**CPVS 90 – 132 HP**  
Inverter Driven Screw

**CPX 10 – 2500**  
Refrigerant Dryers

**FILTER**

### User benefits



#### Built to last

Designed for high efficiency and continuous duty under hard working conditions.



#### High efficiency cooling

Large oversized cooling, designed for demanding conditions.



#### Two stage filtration

Improved double stage intake filtration protects internal components.



#### Energy saving controller

A unique controller, specially programmed for compressor management and energy saving.



#### Accessibility of parts

All consumables on same side of the machine, easy to access.

**CPK 5.5 – 22 HP**  
Compact Screw

**CPA/CPB 5.5 – 30 HP**  
Industrial Screw

**CPG/CPD 40 – 100 HP**  
Industrial Screw

**CPE/CPF/CPG 90 – 355 HP**  
Direct Driven Screw

**CPVR 15 – 75 HP**  
Inverter Driven Screw

**CPVS 90 – 132 HP**  
Inverter Driven Screw

**CPX 10 – 2800**  
Refrigerant Dryers

**FILTER**

**Robust and powerful compressor**

Engineered for high performance:

- Large efficient screw element for high air delivery.
- IP54 high efficiency electric motor.
- Belt drive transmission, high performance V belt drive.
- Two stage filtration with large inlet baffle, protecting your investment.
- Large high efficiency aluminum air/oil cooler.
- High quality flexible oil lines, minimizing leaks.
- Intelligent energy saving control system, simple user interface.
- Simple installation.
- Low noise levels.
- Large easy access for all maintenance.



**Features**

Ducting	The air intake, air outlet and the cooling of the air are all at the same side, which makes it easy for ducting. The machine can be installed against a wall if ducting is performed.
Cooling	A large axial fan with separate motor and oversized oil and air cooler for better cooling.
Filtration	Filtration of the incoming cooling air as well as the air inlet of the compressor through a high efficiency air filter.
Oil separation	The oil vessel and oil filters are designed for separation of the oil to a residual level of 3ppm, and for a minimal pressure drop.



**Look for your quality assurance! Use Chicago Pneumatic Original Parts.**

Chicago Pneumatic is always at your service with comprehensive screw kits:

- Easy
- Guaranteed long lifetime
- Reliable operation
- All-in-one cost effectiveness

