

# Specifications

# Honda Petrol

Model	Pump Displacement	Free Air Delivery	Maximum Pressure	Pump	Honda Engine		Tank Volume	Outlet Size	Noise Level	Dimensions (cm) & Weight			
	L/min [cfm] *	L/min [cfm] *	kPa [psi]	Model [rpm]	Model	Starter	Litres	BSP	dB(A) ^	L	W	H	kg
P18H	430 [15.2]	350 [12.4]	1,000 [145]	PG31 [1.080]	GX200 6.5 hp	Rope Pull	60	1/4"	77	112	45	77	90
P22H	540 [19.1]	440 [15.5]	1,000 [145]	PG41 [900]	GX200 6.5 hp	Rope Pull	75	1/4"	77	113	45	80	112
P22H ES	540 [19.1]	440 [15.5]	1,000 [145]	PG41 [900]	GX200 6.5 hp	Electric <sup>Δ</sup>	75	1/4"	77	113	45	80	115
P30H	805 [28.4]	690 [24.4]	1,000 [145]	PG56 [940]	GX270 9 hp	Rope Pull	125	1/2"	80	141	45	97	189
P30H ES	805 [28.4]	690 [24.4]	1,000 [145]	PG56 [940]	GX270 9 hp	Electric <sup>Δ</sup>	125	1/2"	80	141	45	97	192
P55H ES	1,340 [47.3]	1,015 [35.9]	1,000 [145]	PG101 [740]	GX390 13 hp	Electric <sup>Δ</sup>	140	3/4"	81	156	48	108	257

\* Measured per AS 4637-2006. <sup>Δ</sup> The engine must be connected to a 12 Volt battery (not supplied) to use the electric starter. <sup>^</sup> Measured @ 7 m per AS 2221.1-1979.

## Features and Benefits




### Puma Hi-Flow Pump

Puma's exclusive long-stroke pump design delivers very high flow-rates at low pump speeds. Its full cast iron construction is built tough for reliability and long service life.



### Honda Petrol Engine

Legendary reliability and advanced performance are guaranteed by the Honda GX engine. Auto-idle throttle control regulates the engine speed to minimize fuel use, noise and wear.



### Electric Start

Choose the convenience of an electric start model and avoid the strain of rope pull starting. Each one's built-in alternator can keep the optional 12 Volt battery fully charged.



### 12 Volt Battery Kit Option

Make your electric start compressor independent of its host service truck by specifying this option. The kit includes a maintenance free battery, insulated leads and custom engineered bracket.



### Filter Regulator (P18H & P22H)

The 5 micron filter effectively removes dirt and water from the compressed air stream while the regulator provides accurate pressure control. A Nitto-style coupling is fitted to the air outlet port.



### Puncture Proof Tyres (P18H & P22H)

You'll never be let down by a puncture with these solid rubber tyres mounted on heavy-duty steel wheels. The wide tread profile and ball bearing hub also allow for easy all-terrain handling.



PUMA and the PUMA WILDCAT image are registered trade marks of Puma Industrial Co., Ltd. (Taiwan).

HONDA is a registered trade mark of Honda Motor Co. Ltd. (Japan).



AUTHORIZED PUMA DEALER:

AIR CONNECTION  
3/12-14 TIKALARA ST  
REGENCY PARK 5010  
ABN 40 580 697 8 55



www.puma-air.com.au